



Certificate number: 2410731 (1)

Issued 08/10/2024

Expires 08/10/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Nordisk wavin A/S.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:

Nordisk wavin A/S
Wavinvej 1
Hammel
Denmark



KUKreg4

Product Certificate

Appendix to Certificate number: 2410731

The following products belong to this certificate

PRODUCT DESCRIPTION 'Portfolio' HIU for indirect heating with optional controller options. See model range for differences in models. ATS3 – Without Production Surveillance.
MODEL(S) 3092670 CALEFA I V 40/40 V HIU UK HIU 40 plate HEX heat w. heat valve 40 plate HEX DHW 3094324 CALEFA II V 26/26 V HIU UK HIU 26 plate HEX heat w. heat valve 26 plate HEX DHW 3094325 CALEFA II V 40/26 V HIU UK HIU 26 plate HEX heat w. heat valve 40 plate HEX DHW 3094326 CALEFA II V 60/40 V HIU UK HIU 40 plate HEX heat w. heat valve 60 plate HEX DHW 3094327 CALEFA II V ITC 26/26 V HIU UK HIU 26 plate HEX heat w. weather compen. 26 plate HEX DHW 3094328 CALEFA II V ITC 40/26 V HIU UK HIU 26 plate HEX heat w. weather compen. 40 plate HEX DHW 3094329 CALEFA II V ITC 60/40 V HIU UK HIU 40 plate HEX heat w. weather compen. 60 plate HEX DHW
SIZE: 3/4" BSP.
SCOPE: Manufacturer recommended maximum working pressure 16 Bar & maximum operating temperature 85°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.
MARKING Wavin logo, pressure, temp, model and other technical information on front plate.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES No supply pipe or secondary circuit shall be permanently connected to a closed circuit for filling a heating system unless it incorporates a backflow prevention device in accordance with a specification approved by the regulator for the purposes of this schedule.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes