

Product Range Summary OsmaDrain

Product Description	Nominal Size (mm)	82	110	160
Pipe – solid	P/E Pipe – 3 metre	●	●	●
	P/E Pipe – 6 metre	●	●	●
Pipe – slotted	P/E Pipe – 6 metre		●	●
Coupler	D/S Coupler – for slotted pipe		●	●
	D/S Slip Coupler		●	●
	D/S Pipe Coupler	●	●	●
Socket	S/S Settlement Socket		●	
Sleeve	P/E Protection Sleeve		●	
Adaptors	Rainwater Adaptor – to 68mm round	●		
	D/S Adaptor – to thickwall clay		●	●
	D/S Adaptor – to thinwall clay		●	●
	Rainwater Adaptor – to 68mm round		●	
	Universal Rainwater Adaptor		●	
	D/S Adaptor – 32mm waste pipe		●	
	D/S Adaptor – 40mm waste pipe		●	
	D/S Adaptor – 50mm waste pipe		●	
	Internal Drain Connector – 32/40mm waste		●	
	Internal Drain Connector – 50mm waste		●	
	Internal Drain Connector – to soil stack		●	
Cap	Temporary Site Cap		●	
Reducers	S/S Level Invert Reducer – 82mm OsmaDrain		●	
	S/S Level Invert Reducer – 110mm OsmaDrain			●
Short Radius Bends	S/S Bend – 87.5°	●	●	●
	S/S Bend – 67.5°		●	
	S/S Bend – 45°	●	●	●
	S/S Bend – 30°		●	●
	S/S Bend – 15°		●	●
	S/S Bend – 11.25°		●	
	D/S Bend – 87.5°	●	●	●
	D/S Bend – 67.5°		●	
	D/S Bend – 45°		●	●
	D/S Bend – 30°		●	●
	D/S Bend – 15°		●	●
D/S Bend – 11.25°		●		
Adjustable Bends	S/S Bend – 0° – 30°		●	
	D/S Bend – 0° – 30°		●	

Product Range Summary OsmaDrain

Product Description	Nominal Size (mm)	82	110	160
Long Radius Bends	P/E Long Radius Bend – 90°		●	●
	P/E Long Radius Bend – 45°		●	●
	S/S Long Radius Bend – 87.5° with 900mm spigot		●	
	S/S Long Radius Bend – 45°		●	
	D/S Long Radius Rest Bend – 87.5°			●
	D/S Long Radius Bend – 45°			●
Equal Junctions	S/S Junction – 87.5°	●	●	●
	D/S Junction – 87.5°		●	●
	S/S Junction – 45°		●	●
	D/S Junction – 45°	●	●	●
Unequal Junctions	S/S Junction – 87.5°– 160mm x 110mm			●
	D/S Junction – 87.5°– 160mm x 110mm			●
	S/S Junction – 45°– 160mm x 110mm			●
	D/S Junction – 45°– 160mm x 110mm			●
Anti-Flood Valves	S/S Anti-flood Valve – single valve, for surface water only		●	●
Sealed Access Fittings	S/S Inspection Pipe		●	
	S/S Equal Double Inspection Junction – 45°		●	
Sealed Rodding Eyes	P/E Rodding Eye – Straight – 15kN (1.5 Tonnes)		●	●
	S/S Rodding Eye – 45°– 15kN (1.5 Tonnes)		●	
Screwed Access Fittings	P/E Screwed Access Cover		●	●
	S/S Screwed Access Cover		●	●
	S/S Short Radius Access Bend – 87.5°		●	
	S/S Access Pipe		●	●
	D/S Short Radius Access Bend – 87.5°		●	
	D/S Equal Access Junction – 87.5°		●	
Socket Plugs	Socket Plug		●	
	P/E Socket Plug – closed boss socket		●	
	P/E Socket Plug			●
	P/E Socket Plug – open boss socket		●	
Universal Gully Fittings	S/S Universal Gully Trap		●	
	P/E Plain Hopper		●	
	P/E Vertical Inlet Hopper		●	
	P/E Sealed Access Hopper		●	
	SW/S Plain Hopper		●	
	SW/S Vertical Inlet Hopper		●	
	S/S Bossed Pipe		●	
	Sealed Access Cover		●	

Product Range Summary OsmaDrain

Product Description	Nominal Size (mm)	82	110	160
Bottle Gullies	P/E Access Gully		●	
	S/S Paved Area Gully		●	
	Sealed Cover Plate – for paved area gully only		●	
	Metal Grid Gully Cover – for paved area gully only		●	
	S/S Bottle Gully – 87.5°		●	
	S/SW Bottle Gully – 87.5°– back boss open		●	
	Sealed Access Cover – for bottle gully only		●	
	Bottle Gully Riser – for bottle gully only		●	
	DI Grating – for bottle gully only		●	
Yard Gully	P/E Trapped Yard Gully – 300mm dia		●	
	Grating and Frame		●	
	Perforated Galvanised Catchment Bucket		●	
Suspended Brackating System	Adjustable Pipe Brackating Assembly		●	
	Adjustable Socket Bracket and Brace Assembly		●	
Testing Equipment	Stopper for Testing		●	●
Cleaners, Solvent Cements & Lubricants	Degreasing Cleaner No 1 – 250ml can	●	●	●
	Solvent Cement No 2 – 125ml can	●	●	●
	Soluble Luricant	●	●	●
Spares	Spares	●	●	●