

Product Range Summary

Osma UltraRib

Product Description	Nominal Size (mm)	150	225	300
Pipe	Plain Ended (P/E) – 3 metre	●	●	●
	Single Socket (S/S) – 3 metre	●	●	●
	Single Socket (S/S) – 6 metre	●	●	
Rocker Pipe	S/S Rocker Pipe – 600mm effective length	●	●	●
Couplers	D/S Slip Coupler – for repairs	●	●	●
	D/S Pipe Coupler – for jointing pipe	●	●	●
Adaptors	D/S Adaptor to thinwall Clay Spigot	●		
	S/S Adaptor – 6UR Socket x 160mm BS EN 1401 Spigot	●		
	D/S Adaptor – 6UR Socket x 160mm BS EN 1401 Socket	●		
	S/S Adaptor – 6UR Spigot x 160mm BS EN 1401 Socket	●		
Level Invert Reducers	S/S Reducer – to OsmaDrain BS EN 1401 Spigot	●		
	S/S Reducer – to 150mm UltraRib Spigot		●	
	D/S Reducer – to 225mm UltraRib Spigot			●
Short Radius Bends	S/S – 45°	●		
	D/S – 87.5° – 6UR Socket x 160mm BS EN 1401 Socket	●		
	D/S – 87.5°	●	●	●
	D/S – 45°	●	●	●
	D/S – 30°	●	●	●
	D/S – 15°	●	●	●
Junctions	D/S Equal – 87.5° – to UltraRib Spigot	●		
	D/S Equal – 45° – to UltraRib Spigot	●	●	●
	D/S Unequal – 87.5° – to BS EN 1401 Spigot	●		
	D/S Unequal – 45° – to BS EN 1401 Spigot	●	●	●
	D/S Unequal – 45° – to UltraRib Spigot		●	●
Sealed Access Fittings	P/E Screwed Access Cover	●		
	S/S Screwed Access Cover	●		
Socket Plug	P/E Socket Plug	●	●	●
Road Gully	S/S Road Gully – 450mm diameter x 900mm invert	●		
	S/S Road Gully – 450mm diameter x 750mm invert	●		
Accessories	Joint Lubricant	Suitable for use with all sizes		
	Inflatable Testing Plug	●		
Spares	Ring Seal	●	●	●